

Pneumatic contact fem. with valve 1,6 mm

Specification Pneumatic contact fem. with value 1.6 mm HARTING eCatalogue https://b2b.harting.com/09140006256 HARTING eCatalogue https://b2b.harting.com/09140006256 Kentification Kentification Category Contacts Type of contact Poeumatic contact <td col<="" th=""><th colspan="2" rowspan="2"></th><th>Part number</th><th>09 14 000 6256</th></td>	<th colspan="2" rowspan="2"></th> <th>Part number</th> <th>09 14 000 6256</th>			Part number	09 14 000 6256
Identification Category Contacts Type of contact Pneumatic contact Description of the contact With shut-off Polypropylen Straight Version Female Cechnical characteristics Initing temperature Operating pressure 48 bar Tube inner diameter 1.6 mm Material (contacts) Delrin acetal Material (seal) Buna-N RelKS compliant ELV status compliant China RoHS e REACH ANNEX XIV substances No	Specification				
Category Contacts Type of contact Pneumatic contact Description of the contact With shut-off Polypropylen Straight Description of the contact With shut-off Polypropylen Straight Version Female Cender Female Technical characteristics -40 +80 °C Operating pressure ≤8 bar Tube inner diameter 1.6 mm Material properties Material (contacts) Material (seal) Buna-N RoHS compliant ELV status compliant China RoHS e RACH Annex XVII substances No REACH ANNEX XIV substances No	and the second second	יסר	HARTING eCatalogue	https://b2b.harting.com/09140006256	
Category Contacts Type of contact Pneumatic contact Description of the contact With shut-off Polypropylen Straight Description of the contact With shut-off Polypropylen Straight Version Female Cender Female Technical characteristics -40 +80 °C Operating pressure ≤8 bar Tube inner diameter 1.6 mm Material (contacts) Delrin acetal Material (seal) Buna-N RoHS compliant ELV status compliant China RoHS e REACH Annex XVII substances No REACH ANNEX XIV substances No					
Type of contact Pneumatic contact Description of the contact With shut-off Polypropylen Straight Version Female Gender Female Technical characteristics -40 +80 °C Operating pressure ≤8 bar Tube inner diameter 1.6 mm Material properties Delrin acetal Material (contacts) Delrin acetal RedRS compliant ELV status compliant China RoHS e REACH Annex XVII substances No	Identification				
Description of the contact With shut-off Polypropylen Straight Version Female Gender Female Technical characteristics -40 +80 °C Operating pressure -40 +80 °C Operating pressure -8 bar Tube inner diameter 1.6 mm Material properties Delrin acetal Material (contacts) Delrin acetal Material (seal) Buna-N RoHS compliant ELV status compliant China RoHS e REACH Annex XVII substances No REACH ANNEX XIV substances No	Category	Contacts			
Description of the contact Straight Version Female Gender Female Technical characteristics Female Limiting temperature -40 +80 °C Operating pressure ≤8 bar Tube inner diameter 1.6 mm Material properties Elini acetal Material (contacts) Delrin acetal Material (seal) Buna-N RoHS compliant ELV status compliant China RoHS e REACH Annex XVII substances No REACH ANNEX XIV substances No	Type of contact	Pneumatic co	ontact		
Gender Female Technical characteristics Limiting temperature -40 +80 °C Operating pressure ≤8 bar Tube inner diameter 1.6 mm Material properties Delrin acetal Material (contacts) Delrin acetal Material (seal) Buna-N RoHS compliant ELV status compliant China RoHS e REACH Annex XVII substances No	Description of the contact		Polypropylen		
Technical characteristics Limiting temperature -40 +80 °C Operating pressure ≤8 bar Tube inner diameter 1.6 mm Material properties Material (contacts) Delrin acetal Material (seal) Buna-N RoHS compliant ELV status compliant China RoHS e REACH Annex XVII substances No REACH ANNEX XIV substances No	Version				
Limiting temperature-40 +80 °COperating pressure≤8 barTube inner diameter1.6 mmMaterial propertiesMaterial (contacts)Delrin acetalMaterial (seal)Buna-NRoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNoREACH ANNEX XIV substancesNo	Gender	Female			
Operating pressure ≤8 bar Tube inner diameter 1.6 mm Material properties Material (contacts) Delrin acetal Material (seal) Buna-N RoHS compliant ELV status compliant China RoHS e REACH Annex XVII substances No REACH ANNEX XIV substances No	Technical characteristics				
Tube inner diameter 1.6 mm Material properties Naterial (contacts) Material (contacts) Delrin acetal Material (seal) Buna-N RoHS compliant ELV status compliant China RoHS e REACH Annex XVII substances No REACH ANNEX XIV substances No	Limiting temperature	-40 +80 °C			
Material propertiesMaterial (contacts)Delrin acetalMaterial (seal)Buna-NRoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNoREACH ANNEX XIV substancesNo	Operating pressure	≤8 bar			
Material (contacts)Delrin acetalMaterial (seal)Buna-NRoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNoREACH ANNEX XIV substancesNo	Tube inner diameter	1.6 mm			
Material (seal)Buna-NRoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNoREACH ANNEX XIV substancesNo	Material properties				
RoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNoREACH ANNEX XIV substancesNo	Material (contacts)	Delrin acetal			
ELV statuscompliantChina RoHSeREACH Annex XVII substancesNoREACH ANNEX XIV substancesNo	Material (seal)	Buna-N			
China RoHSeREACH Annex XVII substancesNoREACH ANNEX XIV substancesNo	RoHS	compliant			
REACH Annex XVII substances No REACH ANNEX XIV substances No	ELV status	compliant			
REACH ANNEX XIV substances No	China RoHS	е			
	REACH Annex XVII substances	No			
REACH SVHC substances No	REACH ANNEX XIV substances	No			
	REACH SVHC substances	No			

Page 1 / 2 | Creation date 2019-11-14 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
Commercial data	
Packaging size	10
Net weight	0.72 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27440204 Contact for industrial connectors

Page 2 / 2 | Creation date 2019-11-14 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com