


Han E M Crimp Contact Ag with WW for Q 5



Part number	09 33 000 6195
	03 00 0135
Specification	Han E M Crimp Contact Ag with WW for Q 5
HARTING eCatalogue	https://b2b.harting.com/09330006195

Image is for illustration purposes only. Please refer to product description.

CategoryContactsSeriesHan E [®] Type of contactPCB contactVersionNaleCenderMaleTechnical characteristicsSing and
Type of contactPCB contactVersionGenderMaleTechnical characteristicsOperating current≤16 AContact resistance≤3 mQMaterial propertiesMaterial (contacts)Copper alloySurface (contacts)Silver platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight
VersionGenderMaleTechnical characteristicsOperating current≤16 AContact resistance≤3 mQMaterial propertiesMaterial (contacts)Copper alloySurface (contacts)Silver platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight
GenderMaleTechnical characteristicsOperating current≤16 AContact resistance≤3 mΩMaterial propertiesMaterial (contacts)Copper alloySurface (contacts)Silver platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight
GenderMaleTechnical characteristicsOperating current≤16 AContact resistance≤3 mΩMaterial propertiesMaterial (contacts)Copper alloySurface (contacts)Silver platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight
Technical characteristics Operating current ≤16 A Contact resistance ≤3 mΩ Material properties Copper alloy Surface (contacts) Copper alloy Silver plated compliant with exemption RoHS copper alloy containing up to 4 % lead by weight
Operating current≤16 AContact resistance≤3 mΩMaterial propertiesMaterial (contacts)Copper alloySurface (contacts)Silver platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight
Operating current ≤16 A Contact resistance ≤3 mΩ Material properties Copper alloy Material (contacts) Copper alloy Surface (contacts) Silver plated RoHS compliant with exemption RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight
Contact resistance ≤3 mΩ Material properties Material (contacts) Copper alloy Surface (contacts) Silver plated RoHS compliant with exemption RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight
Material properties Material (contacts) Copper alloy Surface (contacts) Silver plated RoHS compliant with exemption RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight
Material (contacts)Copper alloySurface (contacts)Silver platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight
Surface (contacts) Silver plated RoHS compliant with exemption RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight
RoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight
RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight
ELV status compliant with exemption
China RoHS 50
REACH Annex XVII substances No
REACH ANNEX XIV substances No
REACH SVHC substances Yes
REACH SVHC substances Lead

Page 1 / 2 | Creation date 2019-12-06 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Specifications and approvals

Specifications	EN 60664-1 IEC 61984
Commercial data	
Packaging size	100
Net weight	1.6 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27440204 Contact for industrial connectors

Page 2 / 2 | Creation date 2019-12-06 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com