

* Features

Screen Size	19"
Supporting Resolutions	SXGA (1280 x 1024 dots)
Input Signal	Analog RGB, DVI-D Single Link
	Optional CVBS 1 Channel / S-VHS 1 Channel
Power Input	AC 90~265VAC (47~63Hz)
Dimension (W x H x D)	438 x 363 x 69.5(53) mm
Cutting Size	426.5 x 351.5 mm

* Specifications

Screen Size	19"
Supporting Resolutions	SXGA (1280 x 1024 dots)
Input Signal	Analog RGB, DVI-D Single Link
	Optional CVBS 1 Channel / S-VHS 1 Channel
Auto Detection by Adjustment OSD (On Screen Display)	
Chassis	Front – Aluminum, Rear – Steel
	Optional Color – Ivory, Dark Grey
Mount Type	Panel Mount & VESA Standard ARM Mount
Display Colors	16.7 M
Luminance (cd/m ²)	250 (Typ),
Lamp Life Time	30,000 Hrs
Viewing Angle	85/85/80/80 L/R/U/D (Typ)
Contrast Ratio	1,000 (Typ)
Power Input	AC 90~265VAC (47~63Hz)
Operating Temperature	0 ~ 50 °C
Storage Temperature	-20 ~ 60°C
Dimension (W x H x D)	438 x 363 x 69.5(53) mm
Weight	Net ; 9.9 kg

* Optional Touch Screen

Analog Resistive Type

5-Wire Type

Serial RS-232 Interface

* Ordering Information

SX1900 : 19" TFT LCD Monitor

SX1900-T : SX1900 with Touch Screen

SX1900-V : SX1900 with CVBS/S-VHS